

5% AXIAL LEADED RESISTOR

BRN BLK GRN GLD
1 0 5
 IN HOUSE P/N: _____105
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

1.0M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED RED GRN GLD
2 2 5
 IN HOUSE P/N: _____225
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

2.2M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

YEL VIO GRN GLD
4 7 5
 IN HOUSE P/N: _____475
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

4.7M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN BRN GRN GLD
1 1 5
 IN HOUSE P/N: _____115
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

1.1M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED YEL GRN GLD
2 4 5
 IN HOUSE P/N: _____245
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

2.4M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

GRN BRN GRN GLD
5 1 5
 IN HOUSE P/N: _____515
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

5.1M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN RED GRN GLD
1 2 5
 IN HOUSE P/N: _____125
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

1.2M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED VIO GRN GLD
2 7 5
 IN HOUSE P/N: _____275
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

2.7M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

GRN BLU GRN GLD
5 6 5
 IN HOUSE P/N: _____565
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

5.6M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN ORN GRN GLD
1 3 5
 IN HOUSE P/N: _____135
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

1.3M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

ORN BLK GRN GLD
3 0 5
 IN HOUSE P/N: _____305
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

3.0M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BLU RED GRN GLD
6 2 5
 IN HOUSE P/N: _____625
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

6.2M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN GRN GRN GLD
1 5 5
 IN HOUSE P/N: _____155
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

1.5M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

ORN ORN GRN GLD
3 3 5
 IN HOUSE P/N: _____335
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

3.3M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BLU GRY GRN GLD
6 8 5
 IN HOUSE P/N: _____685
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

6.8M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN BLU GRN GLD
1 6 5
 IN HOUSE P/N: _____165
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

1.6M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

ORN BLU GRN GLD
3 6 5
 IN HOUSE P/N: _____365
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

3.6M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

VIO GRN GRN GLD
7 5 5
 IN HOUSE P/N: _____755
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

7.5M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

BRN GRY GRN GLD
1 8 5
 IN HOUSE P/N: _____185
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

1.8M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

ORN WHT GRN GLD
3 9 5
 IN HOUSE P/N: _____395
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

3.9M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

GRY RED GRN GLD
8 2 5
 IN HOUSE P/N: _____825
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

8.2M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED BLK GRN GLD
2 0 5
 IN HOUSE P/N: _____205
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

2.0M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

YEL ORN GRN GLD
4 3 5
 IN HOUSE P/N: _____435
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

4.3M Ω

POWER 250mW

5% AXIAL LEADED RESISTOR

RED BRN GRN GLD
9 1 5
 IN HOUSE P/N: _____915
 TYPE: Carbon Film
 MAX VOLTAGE: 250 VDC
 TOLERANCE: ±5% ←

9.1M Ω

POWER 250mW